



Electronics Corporation



# S2M

1/4 Watt

**Input: Stereo Unbalanced Line**

**Output: Mono Balanced or Unbalanced Line**

## **Stereo Unbalanced Line Input**

This is a stereo unbalanced 10K Ohms auxiliary line input. The connector is an unbalanced standard phono (RCA type) jack. This input is ideal for CD players, tape decks, tuners or other stereo unbalanced auxiliary level inputs. Tip is signal and ring is ground.

## **Mono Balanced Line Output**

This is a balanced 600 Ohms line output. The output connector is a 3 pin screw Eurostyle connector. This output is ideal for telephone lines, signal processors, amplifiers, or any other units that have a balanced line input. Pin 1 is ground, pin 2 is (-) signal, and pin 3 is (+) signal.

## **Mono Unbalanced Line Output**

This output is designed to supply signal to any unbalanced auxiliary level input like a tape recorder, system monitors, or to another mixer. This output connector is a standard phono (RCA Type) jack. Tip is signal and ring is ground.

## **RoHS Compliant**

**Input Maximum Voltage:** 5Vrms

**Input:** Stereo unbalanced 10K Ohms line level

**Output:** Mono balanced 600 Ohms or unbalanced 10K Ohms line level

**Frequency Response:** 20~20K Hz., <1dBu

**THD+Noise:** <0.05% @ 1K Hz.

**Mounting:** Surface Mounted

**Weight:** 0.5 lbs.

**Dimensions:** 4.5" (L) x 2.5" (W) x 1.3" (H)

**[www.edcorusa.com](http://www.edcorusa.com)**

EDCOR Electronics Corporation

7130 National Parks Highway

Carlsbad, NM 88220

U.S.A.

(575) 887-6790

