




XPWR128-120

Type: Tube Power Transformer

Primary: 120V, 60Hz.

Secondary: 500V (250-0-250)@60mA & 6.3V(3.15-0-3.15)@2A

Schematic



Image




IMAGE REFERENCE ONLY

Specifications:

Total Volt Amperes: 42.6VA

Primary: 120V, 60Hz.

Primary Current: 0.373A

Primary DCR: 7.92Ω

Primary inductance: 1.793H

Secondary Voltages: 500V, 6.3V

Unloaded Voltages: 525.346V, 6.636V

Secondary Currents: 0.06A, 2A

Secondary DCR: 243.8Ω, 0.089Ω

Winding Config: Layer Wound

Core Stack Interleave (1x1)

Dielectric Strength: 2500Vrms

HIPOT Pri.-Sec.: 2000Vrms

120V Temp. Rise: 69.37°F (20.76°C)

Temperature Range: REACH & REACH & CMRT

Leakage Inductance: 0.0034H

Efficiency: 92%

Regulation: 8.14%

Compliance: REACH & REACH & CMRT

Country of Origin United States

Harmonized System Code: 8504.31.2000

Physical

Core Size: EI100 x 1.25in.

Dimensional Drawing: 15000-EI100-125-0XV

Weight: 2.6 lbs.

Bobbin

Material: Nylon 6/6 GF-30

Flammability Rating: Class-HB

Magnet Wire

Material: Nylon coated unrecycled solid copper wire.

Core Material

Material: M6 29 ga. grain oriented lamination steel.

Coil Finishing Wrapper

Material: Polyester film/Non-woven tape.

Secondary Insulation

Material: Clear air dry polyester electrical varnish.

Hardware

Mounting: End Bells

Orientation: Vertical

Terminations

Material: 15 in. (38cm) UL1015, 18 ga. lead wire.

EDCOR Electronics Corporation

7130 National Parks Highway - Carlsbad, NM 88220 - United State